



Transportbügel in Schraubausführung Güteklasse 8 und 10

Bestell-Nr.	Tragfähigkeit	Schraube		Abmessungen							Ovalglied	Gewicht ca.	
		Gewinde	[Nm]	a	b	c	Ød	e	f	g			
	[t]			[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]
Güteklasse 8 – mit Schrauben nach ISO 4017 (DIN 933 / 10.9), 100 % rissgeprüft													
21430053	15,00	M 36	675	175	255	72	39	40	90	110	32x150x 75	9,52	
21430055	20,00	M 42	1000	200	295	90	45	50	116	140	40x190x100	18,47	
21430058	25,00	M 45	1400	200	295	90	48	50	116	140	40x190x100	19,09	
Güteklasse 10 - mit Schrauben mit Innensechskant nach ISO 4762 / 10.9, 100 % rissgeprüft													
21430065	30,00	M 48	1900	200	295	90	50	50	116	140	40x190x100	20,76	
Güteklasse 8 - ohne Schrauben													
21430073	15,00		675	175	255	72	39	40	90	110	32x150x 75	7,40	
21430075	20,00		1000	200	295	90	45	50	116	140	40x190x100	15,10	
21430078	25,00		1400	200	295	90	48	50	116	140	40x190x100	15,10	
Güteklasse 10 - ohne Schrauben													
21430085	30,00		1900	200	295	90	50	50	116	140	40x190x100	15,00	



Tragfähigkeiten

Anschlagart	[t]		[t]		[t]		[t]		[t]	
	1	1	2	2	2	2	3 oder 4	3 oder 4		
Neigungswinkel	0°	90°	0°	90°	0° - 45°	45° - 60°	0° - 45°	45° - 60°		
el	[t]	[t]	[t]	[t]	[t]	[t]	[t]	[t]		
21430052	15,00	15,00	30,00	30,00	21,00	15,00	31,50	22,50		
21430054	20,00	20,00	40,00	40,00	28,00	20,00	42,00	30,00		
21430056	25,00	25,00	50,00	50,00	35,00	25,00	52,50	37,50		
21400058	30,00	30,00	60,00	60,00	42,00	30,00	63,00	45,00		



GK 10 - Nur mit Innensechskantschrauben verwendbar

NEUMANN GMBH
Hebesysteme Fördertechnik

Paul-Ehrlich-Straße 5a
63128 Dietzenbach

Tel. 06074 8504-0
Fax 06074 850412

E-Mail info@neumann-gmbh.com
www.neumann-gmbh.com